

Ground Based Electronic Equipment

Large (Aluminium)

| | |
|-------------------------------|--|
| Volume: | 100 up to and above 1,000 litres |
| Container Construction: | Aluminium |
| Operational Life (estimated): | 9-12months |
| Leakage: | No leak under water |
| Pressure: | Limited to 3psi |
| Climate: | Northern Europe (Multiply desiccant by 3 for Tropical Climate) |
| Seals/Gaskets: | Nitrile Rubber (1 metre long – 3mm diameter) |

Volumes:

| | |
|--------------------|--|
| Up to 100 litres | Combined Humidity Indicator & Desiccator BLD4318/06 For additional air transportation requirements use Relief Valve BLD9215/01 |
| Up to 1,000 litres | Humidity Indicator BLD3058/01-04 Desiccant Port BLD8148, Record Holder BLD7943 optional For additional air transportation requirements use Relief Valve BLD9156 |
| Above 1,000 litres | Humidity Indicator BLD7941, Desiccant Port BLD8148, Record Holder BLD7943 optional For additional air transportation requirements use Relief Valve BLD9156 Optional panel bush BLD8210, for use with indicator |

Desiccator life assuming the equipment has been dry gas purged to Remove hygroscopicity.

For Electronic Equipment silica gel desiccant is recommended.

For additional R.F. Screening requirements please contact our technical office on 020 8965 9281.

We recommend using our Tie down shelving, Kevlok straps and Shockmaster for shock and vibration conditions.