

## Weapons Container

### Small (Aluminium)

Volume:	1 to 50 litres
Container Construction:	Aluminium Casting
Operational Life (estimated):	12-24 months
Leakage:	No leak under water
Pressure:	Limited to 3psi
Climate:	Northern Europe (Multiply desiccant by 3 for Tropical Climate)
Seals/Gaskets:	Nitrile Rubber (1 metre long – 3mm diameter)

### Volumes:

Up to 1 litre	Humidity Indicator BLD5000/01 or R.F.Screened version BLD5000/02, Desiccant sachet BLD7410/04 For additional air transportation requirements use Relief Valve BLD8887/01 or R.F.Screened Valve BLD9314/01
Up to 10 litres	Humidity Indicator BLD5000/01 or R.F.Screened version BLD5000/02, Desiccant sachet BLD7410/06 For additional air transportation requirements use Relief Valve BLD9132/01
Up to 50 litres	Humidity Indicator BLD5000/01 or R.F.Screened version BLD5000/02, Desiccant sachet BLD7410/09 Record Holder BLD3634/01. For additional air transportation requirements use Relief Valve BLD9132

Desiccator life assuming the equipment has been dry gas purged to remove hygroscopicity.

For Weapons Containers we recommend using silica gel desiccant bags BLD7410/01-09. Additional hydrocarbon adsorption units are available on request.

We recommend using our Tie down shelving, Kevlok straps and Shockmaster for shock and vibration conditions.