DRG. No.
BI/D 5406 INST
USED ON

THIRD ANGLE
PROJECTION

290.0

NOTES

FILLED WITH MOLECULAR SIEVES DESICCANT, GRADE 4A, 1/16" PELLETS (LISA SOURCED).

PACKAGING

INNER PRIMARY - WRAP WITH KRAFT PAPER.

PACK WITH INDICATOR PAPER IN 500 GAUGE POLYETHYLENE ENVELOPE & HEAT SEAL.

OUTER - FIBREBOARD CARTON.

MATERIAL ALUM ALLOY SHEET 22 SWG - PERF.	PROTECTIVE FINISH ANODISED & DYED LIGHT BLUE				
		DES. CHANGED	5068	C	19.5.97
		"" PELLETS ADDED	4383	B	10.12.93
				А	23.10.89
EST. WT. —		CHANGE	MOD. No	. ISSUE	DATE
DIMNS IN mm	SURFACE ROUGH TOLERANCES				
SCALE —	· 	PROFILE ± 1.0			
BROWNELL	IDON N.W.10	E .	RAWN	CHKD.	
SUB CONT.		SUB CONT. DRG. REF.			
TITLE		DRAWING No.			
DESICCANT CONTAINER DEHUMIDIFIER (STATIC)		BL/D 5406 INST			