DRG. No. THIRD ANGLE BL/D 7916 INST **PROJECTION USED ON** 60.0 50.0 MAX KEY SLOT 7.0 WIDE x 1 DEEP **%**%% 28 UNEF SILICONE RUBBER LEVEL HUMIDITY INDICATOR 15 & 30% RH GASKET

NOTES

AT 25°C

- 1. FILLED WITH 4A MOLECULAR SIEVES DESICCANT TO BS7444.
- 2. PACKAGED FOR A SHELF LIFE OF 5 YEARS WHEN STORED IN TEMPERATE CONDITIONS.

MATERIAL	PROTECTIVE FINISH		1		
MINTERIORE	THO LOTTE THE ST		+		
ALUM ALLOY	ANODISED	· · · · ·			
	ANODISED	`	<u> </u>		
				Α	14/5/98
EST. WT. —		CHANGE	MOD.No.	ISSUE	DATE
DIMNS. IN mm	SURFACE ROUGH	TOLERANCES	105		
SCALE 1:1	<u> </u>		<u>+</u> 0.5		
BROWNELL LIMITED LONDON N.W.10			DF	AWN J	CHKD.
			<u> </u>		

SUB.CONT. — SUB.CONT. DRG. REF. — DRAWING No.

DESICCANT CONTAINER DEHUMIDIFIER (PANEL MOUNTING)

BL/D 7916 INST